



## Oleum 23% / 65%

### CHEMICAL FORMULA :

$H_2S_2O_7$

### PROPERTIES :

Appearance :	Clear to off white liquid
Sp. Gravity at 30 °C :	1.9056 (Oleum 23 %)
	1.9654 (Oleum 65 %)
Boiling point :	340 °C

Attack many metals with liberation of hydrogen, which is inflammable and forms explosive mixture, Hygroscopic in nature, Oxidizing agent.

### SPECIFICATIONS :

Free $SO_3$	23.0% min. / 65.0 % min.
Iron (as Fe) :	0.05 % max
Residue on ignition	0.20 % max
Sulphur Dioxide	0.02 % max
Chloride (as Cl)	0.002 % max

### APPLICATIONS :

Sulphonating agent for organic and alizarin dyestuff.

Dehydrating agent in nitration reactions. Used for manufacturing dyes & explosives. Used as lab reagents.

### DANGERS AND PRECAUTIONS FOR HANDLING PRODUCT :

Toxic by ingestion

Causes severe damage to eyes, Skin & air passage

Reaction with moist air produces mist, which has severe irritant effect on eyes, skin & air passage.

Store the material in MS tank. Avoid contact with moisture.

Fire risk in contact with organic substance

### PACKING :

Tanker Load.



*Guljag Industries Limited*

Nahata Bhawan, Chopasani Road, Jodhpur - 342003, Rajasthan, (INDIA)  
Phone : + 91-0291-2435581, 3290403 Fax : + 91-0291-2114209 Email : [scd@guljag.com](mailto:scd@guljag.com)