

Battery Grade Sulphuric Acid

CHEMICAL FORMULA :

H₂SO₄

PROPERTIES :

Appearance :	Clear colorless liquid
Sp. Gravity at 30 °C	1.82
Molecular weight	98.08
Boiling point	340 °C

SPECIFICATIONS :

Purity (as H ₂ SO ₄)	98.0% min
Turbidity	20 NTU Max
Iron (as Fe)	20 ppm Max
Residue on ignition	0.06% Max
Lead (as Pb)	0.005% Max
Arsenic (as As)	0.00012% Max
Chloride (as Cl)	0.001% Max
Selenium (as Se)	0.002% Max
Manganese (as Mn)	0.0001% Max
Copper (as Cu)	0.003% Max
Zinc (as Zn)	0.003% Max
Oxidisable impurities (as SO ₂)	0.02% Max
Nitrates, Nitrites & Ammonia as (N)	0.003% Max

Applications :

As battery acid.
For manufacturing of specialty chemicals.
Drugs & drug intermediate.
Food grade color, dyes & Chemicals.

DANGERS AND PRECAUTIONS FOR HANDLING PRODUCT :

Toxic.
Causes severe damage to eyes. Skin & air passage.
Reaction with moist air produces mist, which has severe irritant effect on eyes, skin & air passage.
Store the material in SS tank. Avoid contact with moisture.
Fire risk in contact with organic substances.

PACKING

Tanker Load, HM HDPE Carboys of 35/50 Kg.



Guljag Industries Limited

Nahata Bhawan, Chopasani Road, Jodhpur - 342003, Rajasthan, (INDIA)
Phone : + 91-0291-2435581, 3290403 Fax : + 91-0291-2114209 Email : scd@guljag.com